






Übersicht für Absetzbehälter nach DIN 30720 (3 bis 15 m³)

(technische Angaben unter Vorbehalt)

lichte Behältermaße in mm			Blechmaße Boden				Stapel- höhe ca.	Bemerkung, Skizze	Typ	Leer- Gewicht*	Art.-Nr. Lübben
Länge	Breite unten/oben	Höhe	Schütten- Höhe	Breite	Länge	Breite					
2550	1590/1690	900	650	1620	1730	520	Asymmetrisch, stapelbar offen 	A – 3,0 m ³	475 Kg	M 001	
2800	1590/1690	1000	650	1620	1730	465		A – 4,0 m ³	550 Kg	M 002	
3000	1590/1690	1200	850	1620	1730	520		A – 5,0 m ³	600 Kg	M 003	
3150	1590/1690	1300	850	1620	1730	530		A – 5,5 m ³	635 Kg	M 004	
3500	1590/1690	1400	850	1620	1930	630		A – 7,0 m ³	715 Kg	M 006	
4100	1590/1690	1700	1050	1620	2230	930		A – 10,0 m ³	945 Kg	M 008	
4320	1590/1690	2020	1170	1620	2230	1250		A – 12,0 m ³	1105 Kg	M 010	
4300	1690/1690	2170	1170	1720	2230	nicht stapelbar		A – 13,0 m ³	1150 Kg	M 011	
4900	1690/1690	2200	1450	1720	2830			A – 15,0 m ³	1340 Kg	M 013	
2550	1590/1690	900	650	1620	1730	520		Asymmetrisch, stapelbar, offen, schüttenseitig Klappe 	AK – 3,0 m ³	540 Kg	M 029
2800	1590/1690	1100	850	1620	1730	570	AK – 4,0 m ³		615 Kg	M 030	
3000	1590/1690	1200	850	1620	1730	520	AK – 5,0 m ³		670 Kg	M 031	
3150	1590/1690	1300	850	1620	1730	530	AK – 5,5 m ³		705 Kg	M 032	
3500	1590/1690	1400	850	1620	1930	630	AK – 7,0 m ³		785 Kg	M 034	
4200	1590/1690	1700	1050	1620	1930	930	AK – 10,0 m ³		1000 Kg	M 036	
2550	1590/1690	900	650	1620	1730	520	Symmetrisch, stapelbar, offen 		S – 3,0 m ³	470 Kg	M 080
2800	1590/1690	1100	850	1620	1730	570		S – 4,0 m ³	555 Kg	M 081	
3000	1590/1690	1200	850	1620	1930	520		S – 5,0 m ³	630 Kg	M 082	
3150	1590/1690	1300	850	1620	1930	530		S – 5,5 m ³	675 Kg	M 083	
3750	1590/1690	1400	1050	1620	1930	630		S – 7,0 m ³	780 Kg	M 085	
4100	1590/1690	1700	1200	1620	2230	930		S – 10,0 m ³	950 Kg	M 087	
2550	1590/1690	900	900	1620	1730	520		Symmetrisch, stapelbar, offen, hohe Schütte 	S – 3,0 m ³ (HS)	495 Kg	M 090
2800	1590/1690	1100	1100	1620	1730	620	S – 4,0 m ³ (HS)		580 Kg	M 091	
3000	1590/1690	1200	1200	1620	1930	520	S – 5,0 m ³ (HS)		645 Kg	M 092	
3150	1590/1690	1300	1300	1620	1930	530	S – 5,5 m ³ (HS)		685 Kg	M 093	
3750	1590/1690	1500	1500	1620	1930	730	S – 7,0 m ³ (HS)		840 Kg	M 095	
4200	1590/1690	1700	1700	1620	2230	930	S – 9,0 m ³ (HS)		1005 Kg	M 096	
4200	1590/1690	1850	1850	1620	2230	1080	S – 10,0 m ³ (HS)		1055 Kg	M 097	
2600	1590/1690	1000	800	1620	1730	550	Symmetrisch, stapelbar, gedeckt, 2 federentlastete Deckel, nach Kundenwunsch in Stahl o. PVC 		SD – 3,0 m ³	675 Kg	M 070
3000	1590/1690	1250	850	1620	1730	730		SD – 4,0 m ³	725 Kg	M 071	
3390	1590/1690	1250	900	1620	1930	630		SD – 5,0 m ³	800 Kg	M 072	
3500	1590/1690	1400	1050	1620	1930	780		SD – 5,5 m ³	860 Kg	M 073	
3750	1590/1690	1500	1180	1620	1930	790		SD – 7,0 m ³	930 Kg	M 075	
4250	1590/1690	1850	1500	1620	2230	1140		SD – 10,0 m ³	1175 Kg	M 077	
4250	1590/1690	1875	1200	1620	2230	1165		SD – 10,0 m ³ / SH=1200	1175 Kg	M 077	

* Leergewicht +/- 10% Toleranz